

MADISON

Specification Sheet

Safety Edge
(#5-Denim)

**Uni-Flow
Edgeless**
(#13-Metallic)

Application –
Construction –

Indoor and outdoor.

“Never-Fray” needlepunch construction eliminates the need for edging. Matting can be cut to any size or shape transitioning seamlessly from one to the next.

Texture –
Face Fiber –

Wide rib.

100% Solution dyed UV stabilized polypropylene for maximum stain, fade resistance and anti-static.

Face Weight –

37 oz/sq yd is more than twice the weight of the average rental runner resulting in more water retention, durability, crush resistance, and aggressive soil removal.

Total Weight –
Total Height –
Backing –

.5 lb per square foot.

(.37) inches (variable).

Modified rubber. Non yellowing and non staining. Easily rolls and unrolls flat while reducing mat “creeping” on hard floors. Velcro available for use on carpet.

Sizing –

Up to 13'-2" x 80' in a single piece enables us to manufacture any size or shape in the largest of lobbies.

Flammability –
Water Retention –

Passed (DOC-FF-1-70) Pill test.

(.57) gallons per square yard. Outperforms matting whose claim to fame is water retention.

3-Year Warranty –
Installation –

100% in first year, 50% in second year, 25% in third year.

Easy to self-install with a mat knife. Optional on site installation by a PROFORM certified master installer is available.

Storage Cores –

Optional Heavy Duty fiber storage cores insure that matting is ready to lay flat without curling. (Always store carpet side out.)

Edging Options –

Safety Edging: A 1.5" vinyl reducer which is applied with glue and stitched, with mitered corners and reinforced with vinyl corner supports.

Uni-Flow: Our frayless construction allows the elimination of edging, creating the elegant appearance of an area rug and a seamless transition from one mat to the next. (Most economical, attractive and safe).

Heat bevel: Edge is melted at a 45° angle.

Cleaning –

Regular vacuuming, carpet extraction or bonnet cleaning as needed.


Available in the following colors:



#1 Onyx



#3 Fawn



#2 Chestnut



#13 Metallic

LEED: Possible LEED-NC credits: MR Credit 4 (1-2 points), IEQ Credit 4.1 (1 point)
Recycled Content: 15% post-consumer

www.proformmat.com • Email sales@proformmat.com • Toll 888.331.3100

*Because you never get a second
chance to make a first impression.*